

BX306Z GNSS RTK Board

GPS L1/L2, GLONASS G1/G2, BeiDou B1/B2

BX306Z is a cost-efficient GNSS RTK board for cm-level positioning and accurate raw measurements output, which can be integrated with autopilots and inertial navigation units. BX306Z board supports three constellations to improve the continuity and reliability of the RTK solution even in harsh environment. It features powerful compatibility with other GNSS boards in the market by flexible interfaces, smart hardware design and popular log/command formats.

Key Features:

- Supports three constellations, six frequencies
 - GPS L1/L2, GLONASS G1/G2, BeiDou B1/B2
- Supports up to 20Hz RTK solution and raw data output
- IMU raw data output
- Pin to Pin compatible with Trimble BD970
- LOG & Command compatible with Novatel Protocol
- Supports PPS output and event mark input.
- Serial ports with LVTTL and RS-232 level
- Data output: NMEA-0183 and Tersus Binary format
- Supports logging of raw observation data
- Correction: RTCM 2.x/3.x/CMR/CMR+





Technical Specifications

Performance Specifications

- FrequenciesGPS L1/L2, GLONASS G1/G2, BeiDou B1/B2
- Standard Positioning Accuracy
 - Horizontal(RMS).....1.5m
 - Vertical(RMS).....3.0m
- RTK Positioning Accuracy
 - Horizontal(RMS).....10mm+1ppm
 - Vertical(RMS).....15mm+1ppm
- Observation Accuracy
 - C/A Code(zenith direction).....10cm
 - P Code(zenith direction).....10cm
 - Carrier Phase(zenith direction).....1mm
- Time to First Fix(TTFF)
 - Cold Start.....<50s
 - Warm Start.....<30s
- Timing Accuracy (RMS).....20ns
- Velocity Accuracy (RMS).....0.03m/s
- Initialization(typical).....<10s
- Initialization Reliability.....>99.9%
- Differential Data Format.....RTCM 2.x/3.x/CMR/CMR+
- Max Update Rate.....20Hz

Communication

- Serial Ports.....LVTTTL x1, RS232 x1
- USB Ports.....USB device x1
- CAN Ports.....ISO/DIS 11898 x2 *
- PPS Ports.....LVTTTL x1
- Event Mark.....LVTTTL x2 *
- Ethernet.....10/100M Base-T x1 *

Physical Characteristics

- Input Voltage.....3.3V DC
- Power Consumption(typical).....2.9W
- Active Antenna Input Impedance.....50Ω
- Size.....100x60x12mm
- Weight.....44g
- Antenna Connector.....MCX female x1
- COM Baud Rate.....Up to 921600bps
- Operating Temperature.....-40°C ~ +85°C

* This port's function is related to FW version.

Information and related materials are subject to change without notice. © Copyright 2018 Tersus GNSS Inc.