



SENSOR SPECIFICATIONS:

Laser Scanner	RIEGL VUX-1LR or VUX-1UAV
Inertial Navigation System (INS)	IGI Compact MEMS (ROBIN) or FOG (PRECISION upgrade)
GNSS Receiver	Antcom L1/L2 antenna
Standard Camera	PhaseOne iXU-1000 2 x downward, (RGB and NIR) 1 x oblique

MOUNTING OPTIONS:

Eurocopter AS350/AS355:

AirFilm Model AFSP-1 (STC Number SR01785LA)

Bell 206/407:

AirFilm Model G1-1 (STC Number SR01654LA)

POWER:

Input Voltage 24V ± 30%

Helipod Power-Splitter cable

Connect scanner and RCU to aircraft via voltage stabiliser

All power & data interface cables

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature:	0°C to + 40°C
Storage Temperature:	-40°C to + 60°C
Relative Humidity:	95% non-condensing
Altitude:	10,000ft

The laser scanner RIEGL VUX-1 meets or exceeds the requirements of the following European Standard:
EN 61326-1:2006: Electrical equipment for measurement, control and laboratory use
Protection class: IP64, dust and splash-proof

SCANNER SPECIFICATIONS - VUX-1LR:

Scanner Max Range (Slow Speed*/Refl 80%)	1350m
Scanner Max Range (High Speed*/Refl 80%)	370m
Scanning Speed	10-200/sec
Field of View	330°
Max Effective Measurement Rate	750,000meas/sec
Scanner Precision	10mm

NAVIGATION SPECIFICATIONS - MEMS IMU:

Position	0.02m
Velocity	0.005m/s
Roll/Pitch	0.015°
True Heading	0.03°
Gyro-Bias	1°/h
Gyro-RW	0.07°/√h
Accelerometer Bias	0.1mg
Data Rate	400Hz

CAMERA SPECIFICATIONS:

Resolution	11,608 x 8708 (100MP)
Frame Rate	1sec
Lenses Available	40 to 80mm
Pixel Size	4.6µm

SYSTEM WEIGHT

Pod only	15kg
Scanner and IMU	7kg




MEASUREMENT PRINCIPLES

Time-of-flight measurement

Echo signal digitisation

Online waveform and processing

Multiple time-around processing



SOFTWARE:

MMCAPTURE: Touchscreen interface to allow the scanner, camera and navigation system to be controlled and visualised in realtime.

OUTPUT DATA GENERATION: Sensor data is managed by MMProcess, GrafNav & AEROoffice. Export geo-referenced data into a multitude of different, user defined coordinate systems.

APPLICATION SOFTWARE: Output data can be visualised and used for different applications using Terrasolid software. Terrasolid has been designed for the post-processing and visualisation of laser, trajectory and image data. Running within Bentley Microstation, Terrasolid's applications provide versatile and capable tools for surveyors, civil engineers, designers and planners.

ROBIN +WINGS CONTROL UNIT



The ROBIN +WINGS Ruggedised Control Unit (RCU) has an integrated power converter and is designed to be connected directly to either standard aircraft/helicopter bus power.

If the aircraft used complies with the EURO 5/6+ regulation a secondary battery system may be required to allow the system to work during periods of low voltage alternator output.

The RCU houses an integrated i7 Windows based PC. It is provided with a separate 10" touchscreen monitor and has 2 x 1TB data storage drives which can be expanded for larger projects.

AIRBORNE CAMERA SYSTEM



We recommend the PhaseOne iXU range for use in the ROBIN +WINGS airborne pod. The lightest in its class, the iXUs are purpose built aerial survey medium format cameras.

The iXU range supports mid exposure signal collection for GNSS/IMU synchronisation and the typical survey FMS systems for automated release, FMC speed input and metadata interfacing.

The ROBIN +WINGS pod can support up to three (2 x downward, 1 x oblique) PhaseOne cameras and they are available in RGB and NIR configurations.



ROBIN +WINGS can be upgraded to a ROBIN PRECISION system for projects requiring greater accuracy. ROBIN PRECISION features a fibre optic IMU making it more suitable for detailed topographic surveys, city modelling and construction or mining environments where GNSS conditions are challenging.



WHAT TO EXPECT FROM 3D LASER MAPPING:

Industry Leading Systems Integration

Standard & Advanced Training at Your Location - incl ROBIN set up, data capture, processing including Terrasolid software training

Unrivalled Technical Support: Online, Email & Telephone



INFO@3DLASERMAPPING.COM

WWW.3DLASERMAPPING.COM/ROBIN

TEL: +44 (0) 1949 838004

ROBIN

WALK | DRIVE | FLY

MAP EVERYWHERE IN 3D

ONE SYSTEM
MULTIPLE
MOUNTING
OPTIONS



WALK

Backpack Construction

Carbon fibre frame

Freestanding design when not in use

Lightweight padded harness with waist strap

Fully adjustable

Heavy duty straps with quick-release

Components

VUX-1HA Laser Scanner

Dual GNSS Receiver

Ruggedized GETAC tablet computer

FLIR Grasshopper 3 12MP camera



Additional batteries can be 'stacked' to allow extended duration scanning across larger areas.



Swivel camera mount

Stackable battery system - PAGLINK V-Mount Li-Ion 96

Ethernet data cable for scanner and INS


Option to upgrade IMU - ROBIN PRECISION

APPLICATIONS:

Easy to mount and operate, the ROBIN backpack configuration has been designed to be used by a single operator. WALK mode is ideal for applications where access for vehicles is restricted or terrain is difficult, such as railway slopes or areas with woodland or dense vegetation.

ROBIN WALK mode is suited to applications such as asset mapping, forestry, heritage mapping and geohazard monitoring.

With a simple to use 'quick-release' system, it takes less than 5 minutes to change the ROBIN system from WALK to DRIVE mode, allowing for multiple scans to be completed of the same area in the same day.



DRIVE



Easy transition between WALK & DRIVE mode; designed for use by a single operator.

Vehicle Mount Construction

Carbon fibre roof mounting frame

Freestanding design when not in use

Easy fitting to Thule 'Aerobar' or 'Squarebar' roof bars

Quick release fitting plate positioned at 20° or 40° angle

Robust dual antenna fittings

Components

VUX-1HA Laser Scanner

Dual GNSS Receivers

Ruggedized GETAC tablet computer

FLIR Grasshopper 3 12MP camera

Option to upgrade to +PANORAMIC camera set up

Powered directly from vehicle power or battery box

Ethernet data cable for scanner and GNSS/INS

Option to upgrade IMU - ROBIN PRECISION





APPLICATIONS:

Improve the safety of your surveys with DRIVE mode. With a robust and stable mounting system and in-car power option, DRIVE allows the ROBIN system to be mounted to almost any vehicle, making it suitable for the following applications:

- Highway Mapping
- Urban Asset Management
- Rail Infrastructure Mapping

For city surveys or large civil engineering projects, the ROBIN +PANORAMIC add-on can provide a 360° spherical view for enhanced imaging and retrospective analysis of a site. An optional optical odometer can be supplied for more challenging project needs.



FLY

Airborne LiDAR systems are traditionally only suitable for being mounted onto aircraft. ROBIN +WINGS takes the flexibility of the standard ROBIN system to new heights, with a simple to perform transition between WALK, DRIVE & FLY functions.

ROBIN +WINGS integrates the standard components of the ROBIN system with an extended capacity hard drive and control unit which allows the system to be powered by the aircraft's power supply. The addition of three PhaseOne aerial cameras allows for enhanced imagery to be collected to support the creation of high-density point clouds backed up by high-resolution geo-referenced images.

The ROBIN system's flexibility means that data sets can be combined from WALK, DRIVE and FLY surveys, providing accurate and detailed information from both the ground and air.


The +WINGS add-on works with both single pole and nose helicopter mounts and can improve surveying results in a range of sectors, including forestry, environmental monitoring and transportation infrastructure mapping.



+WINGS HELIPOD:

The ROBIN +WINGS add-on includes a robust and stable HeliPod which is designed to be carried on the AirFilm utility mount. The ruggedized control unit replaces the standard control tablet to provide both system power, control functions and extended data storage.

Inside the pod, there are three pre-defined camera slots - two downward facing (RGB & NIR) and one oblique. These slots are designed to fit the PhaseOne iXU 1000 aerial camera systems which feature the CMOS sensor to enable image capture in lower light conditions. The iXU 1000 also has a higher image resolution, wider ISO range and faster capture speed than any other medium format camera system on the market.



Standard System Physical Characteristics

Size	350mm x 175mm x 150mm
Helipod Weight	8KG

Fitting/Mounting Requirements

Air Film AFSP-1 or Similar
Tyler or Dovetail

Helipod Certification

FAR-27 Compliance Checklist
Mass Balance and Load/Stress Calculations
Airworthiness Report
Installation instructions
Flight Manual

Fits the following components

1 x VUX-1LR Laser Scanner
1 x GNSS/INS
1 x Antenna
Up to 3 cameras, 2 x downward facing, 1 forward facing

Components


Aluminium main frame	ROBIN control unit
Shock isolated sensor mount for stability	HeliPod Power - Splitter Cable
Satcom antenna	Carbon fibre honeycomb panels



APPLICATIONS

Airborne LiDAR systems make it possible to collect highly accurate topographic data much faster, making projects spanning large areas more cost-effective. Low altitude corridor mapping produces dense and accurate point cloud data, even through dense vegetation, allowing for enhanced DTMs and DEMs to be created of typically inaccessible areas. The ROBIN +WINGS add-on is ideal for the following applications:

- Forestry management & planning
- Flood mapping & modelling
- Environmental monitoring
- Utility & Infrastructure mapping



CERTIFICATION IS IN COMPLIANCE WITH THE STC FOR THE AFSP-1



PERFORMANCE	Compact MEMS IMU	Compact FOG IMU
Position	0.02m	0.02m
Velocity	0.005m/s	0.005m/s
Roll/Pitch	0.015°	0.008°
True Heading	0.03°	0.010°
Gyro-Bias	1°/hr	0.03°/hr
Gyro-Random Walk	0.07°/√h	0.005°/√h
Accelerometer Bias	0.1 mg	0.3mg
Data Rate	400Hz	128Hz
PERFORMANCE*	Compact MEMS IMU	Compact FOG IMU
Position	0.3m	0.1m
Roll/Pitch	0.018°	0.008°
True Heading	0.03°	0.015°

*Compact IMU/GNSS system performance after 60 seconds GNSS outage

SURVEY-GRADE MOBILE MAPPING

The ROBIN PRECISION upgrade features a fibre optic (FOG) IMU making it more suitable for detailed topographic surveys, city modelling and construction or mining environments where GNSS conditions are more challenging.

Generally speaking, FOG IMUs have better accuracy than traditional MEMS (Micro Electromechanical System). In particular attitude accuracy is higher and gyro random walk is less which leads to reduced drift when there is no satellite coverage.

ROBIN PRECISION can be used in WALK, DRIVE and FLY set-ups combined with +PANORAMIC and +WINGS extensions for projects requiring greater accuracy.



ROBIN +PANORAMIC is designed for extending the ROBIN system capabilities especially for road and city survey applications.

ROBIN +PANORAMIC includes everything from the standard system set-up, in addition to a FLIR Ladybug5 panoramic camera with additional mounting suitable for use with the ROBIN standard vehicle mount. An optional optical odometer can be supplied for more challenging project needs.


+PANORAMIC comes with a the ruggedised ROBIN Control Unit (RCU) which includes integrated system power management for connecting directly to the vehicle power.

The Ladybug5 panoramic camera has six cameras and can capture at a rate of up to 5 frames per second,uncompressed. Each image is accurately time-stamped by the GNSS/INS allowing geo-referenced image production.



CAMERA SPECIFICATIONS:


Resolution	2048 x 2448 - 30 MP (6 Sensors x 5MP)
Frame Rate	5 frames per second uncompressed
Lens Field of View	90% of full sphere
Shutter	2.02 ms to 2 seconds
Spherical Distance	Calibrated from 2m to infinity
Focus Distance	Objects have an acceptable sharpness from ~ to °



SECTORS

Laser scanning has a wealth of benefits for many sectors and projects. From creating accurate three dimensional models of buildings to mapping and identifying assets on major highways, LiDAR applications are growing in scope and popularity.

3D Laser Mapping are at the leading edge of innovation when it comes to mobile laser scanning systems. We have worked with clients across the world to create systems and software to deliver exceptional results in the field. Our mobile LiDAR systems are created to make data acquisition easy and straightforward for a single operator, meaning that costs are saved on surveying personnel as well as scanning duration.



Pre-construction specialist Central Alliance purchased ROBIN in 2016:

“ROBIN will give us the ability to improve our service offering in a variety of ways - from faster deployment in an emergency situation, to enhancing our existing airborne capabilities, ROBIN’s versatility and forward compatability was crucial in the decision making process.”

Richard Pidcock - Technical Director, Central Alliance

“ROBIN means that we will be able to collect more data in a shorter period of time, with less people, even in difficult to access locations. ROBIN also enables Central Alliance and their clients to meet health & safety obligations by doing everything reasonably practicable to minimise exposure and therefore risks associated with staff on site.”

Rachel Massey - Group Business Director, Central Alliance



SECTORS

From flood mapping to carrying out environmental impact assessments, LiDAR systems provide enhanced intelligence to help make informed decisions, even in the toughest of environments. ROBIN allows operators to map on the move in difficult to reach locations such as coastlines, forests and agricultural areas via the unique backpack mount or the ROBIN +WINGS helipod upgrade.

Using a mobile mapping system means that projects can be completed around 80% faster than when using Terrestrial Laser Scanners. ROBIN, take around five minutes to initialise – around the same time it would take to set up a TLS scanner and mount it to a tripod; yet once the system is set up, it can continue to scan for as long as the data capacity will allow.

ROBIN's flexibility also offers the ability to change between mounting options in minutes. The fast and easy transition between WALK | DRIVE | FLY means that multiple surveys can be completed in a single day.



Texo Drone Survey & Inspection:

“Texo DSI has always been a company that stays at the forefront of the very latest technology. Having previously worked with scanner data both terrestrially and airborne we quickly recognised the merits of combining LiDAR with UAV technology. The ability to rapidly collect highly detailed data via UAV, backpack and vehicle keeps us way ahead of the competition”

James Arnott - Principle Systems Officer, Texo Drones Survey & Inspection



Grasshopper 3
12MP Camera

Protective
Pod

Carrying
Handles

Swivel Camera
mount

Power Input

System Power
Switch

Primary GNSS
Antenna

VUX Laser Scanner

Ethernet
Data Cable for
Scanner & INS

Secondary GNSS
Antenna

Exhaust Fan
Cover

Circuit
Breaker (10A)

SYSTEM CHARACTERISTICS

Control Unit for +PANORAMIC & +WINGS

Touchscreen Power,
HDMI & USB3

Camera Power
& USB3 Data

Power & Ethernet
for pod

Power Input
(from vehicle)

Voltmeter

Removable
1TB (SSD) Data
Storage Drives



SYSTEM OPTIONS

	ROBIN WALK DRIVE FLY	PRECISION	+PANORAMIC	+WINGS
2cm Accuracy with Good GNSS	✓	✓	✓	✓
High Accuracy Level in Restricted GNSS (Upgraded IMU)	✗	✓	Optional	✗
Panoramic Camera	✗	✗	✓	✗
Car & Backpack Mounts	✓	✓	✓	Optional
Control Unit for Data Storage	Optional	Optional	✓	✓
Helicopter Pod & Cables	✗	✗	✗	✓
Odometer	✗	✗	Optional	✗
High resolution medium format camera (50MP-1000MP)	✗	✗	✗	Optional
Powered by mobile, stackable batteries	✓	✓	✗	✗
Powered from vehicle power	✓	✓	✓	✓



ROBIN
WALK | DRIVE | FLY



MAP EVERYWHERE IN 3D

3Dlaser
mapping

UK & EUROPE:

Ranch House, Chapel Lane
Bingham, Nottingham,
NG13 8GF
UK
+44 (0) 1949 838 004
info@3dlasermapping.com

ASIA PACIFIC:

Level 3,
267 St Georges Terrace
Perth WA 6000
Australia
+61 (0) 8 9261 7703
perth@3dlasermapping.com

AFRICA:

Ground Floor, Lakeview Building
1277 Mike Crawford Avenue
Centurion, Gauteng, 0157
South Africa
+27 (0) 12 683 8766
info@3dlasermapping.co.za

US & CANADA:

4600 South Syracuse, 9th Floor,
Denver, Colorado
80237-2719
United States
+1 (0) 720 214 3554
denver@3dlasermapping.com